Equipment Inspection	
☑ Required Lighting	▼ Brake
Headlights (N.C.G.S. § 200-129) Brake Lights (N.C.G.S. § 20-129.1) Directional Signals (N.C.G.S. § 20-125.1)	A visual inspection ONLY shall be conducted for vehicles NOT subject to Federal Inspection Requirements.
▼ Tires	▽ Axe
▽ Broom	✓ Bolt Cutter
▼ Shovel	▼ Flares - Six (6)
	✓ Snatch Blocks - Two (2)
✓ Wrecking Bar or Auto Power Machine	✓ Amber Flashing Light (N.C.G.S. § 20-130.2)
Recovery Lights or Spot Lights on Rear of Wrecker	✓ Current County Map
▼ Fire Extinguisher	☑ Oil Dry (5 lb. Bag)
Reflectorized Safety Vest (For Wrecker Driver)	Current State Inspection (or Federal Inspection for Large Wreckers)
☑ Air-Line Connector and Hose	☑ Light Hook-Up and Line (For Towed Vehicle)
Required Equipment and Specifications GVWR Rating of 26,001 lbs. (Minimum) Minimum Lift 40,000 lbs. Tandem Axles, or Cab to Axle Length of no less than 102	
 A sufficient length of wire rope (cable) with a working loa that meets or exceeds the pulling capacity of the power Automatically Locking Airbrake 	
ENF-500 - CVSA Inspection Number:	
CVSA Decal Number :	
Out-of-Service Decal Number:	

(If Applicable)